

# SECURAMAX<sup>®</sup>

## CLAMP JOINT CONNECTORS



- **Sizes:** 1/2–24" (15–600 mm)
- **Pressures:**  
16,000 psi (110 MPa)
- **Materials:**  
Carbon & Stainless Steel  
Specialty & Exotic Alloys
- **Connections –**  
Butt Weld, Socket Weld,  
Threaded and Special

### SECURAMAX

835 Fourth Line, Oakville  
Ontario, Canada L6L 5B8

Tel.: (905) 842-1723

Fax: (905) 842-9125

E-mail: [securmax@idirect.com](mailto:securmax@idirect.com)

DIVISION OF

# VELAN



---

# THE SECURAMAX CLAMP JOINT

---

## APPLICATIONS

- Oil & Gas Wellheads
- Offshore Drilling & Operating Rigs
- Fossil & Nuclear Power Generation
- Petrochemical Refining & Processing
- Synthetic Fuel Processing
- Coal Gasification & Liquefaction

## FEATURES

- Low Weight Joint
- High Pressure / Compact Joint
- Fast Assembly and Dismantling
- Reusable Seal Ring
- Positive Pressure Metal to Metal Self-Energized Seal Design
- No Bolt Alignment Necessary for Assembly

## BENEFITS

- Lower Pipe Stresses
- Maximum Pressure Integrity
- Reduced Maintenance and Initial Installation Costs
- Low Spare Parts Inventory
- Positive seal at any Pressure
- No welding fixtures required for field pipe fabrication

### SECURAMAX

835 Fourth Line, Oakville  
Ontario, Canada L6L 5B8

Tel.: (905) 842-1723

Fax: (905) 842-9125

E-mail: [securmax@idirect.com](mailto:securmax@idirect.com)

DIVISION OF  
**VELAN**